



### Additional ComfortStar™ Patio Door Features:

1. Additional 82-1/2" inch standard height
2. Designed to meet energy codes out 2030, U value as low 0.14 imp, (0.85 metric)
3. 4-5/8" inches frame depth with nail fin, optional jamb extensions available (standard 5 7/8" frame depth)
4. Multi-stage sealed interlock providing superior water and air performance
5. Additional seals between the frame and sash maintains performance under severe conditions
6. Contemporary "straight line" design
7. Stiffer sash with more internal walls
8. Heavy duty new roller design provides smooth and easy operation even in triple glazed option
9. Increased resistance against heat induced distortion
10. Mechanically fastened frame and fusion welded sash

DOOR NAME	GLAZING LAYERS	GLASS OPTION	GAS	AIR SPACE	U-FACTOR (IMP)	U-FACTOR (M)	SHGC	AIR VALUE	ER
3300 Patio Door	Double	Clear-180	Argon	5/8"	0.29	1.65	0.53	0.23	34
	Triple	Clear-180-Clear	Argon	1/4" - 1/4"	0.29	1.65	0.48	0.23	31
	Triple	Clear-180-Clear	Krypton	1/4" - 1/4"	0.24	1.36	0.48	0.23	37
ComfortStar™	Double	Clear-180	Argon	1/2"	0.27	1.53	0.53	0.5	36
	Triple	Clear-180-Clear	Argon	1/2" - 1/2"	0.22	1.25	0.49	0.5	40
	Triple	Clear-180-180	Argon	1/2"	0.18	1.02	0.45	0.5	43